

Technical Data Sheet Issue: 10-07-2014

	PN-2000 (in case set)
Properties:	<i>PN-2000</i> is a small, light, pneumatically-powered 2K caulking gun for the processing of 395 ml dual cartridges, for example for <i>PUR-O-STOP FS-F</i> .
Technical data:	Mixing ratio:1 : 1, 2 : 1Working pressure:0 - 6 barDimensions:length 58 x width 38 x heigth 26 cmWeight:approx. 8 kg
Processing:	For information on using the caulking gun in case set set please refer to the operation instructions of <i>PN-2000</i> .
Safety information:	Wear protective gloves, protective clothing and eye or face protection during injection work. Before operation start-up the caulking gun it is necessary to inform about the safety instructions. For further information please refer to the operation instructions.
Packaging:	The case set contains the following elements:
	 1 pc PN-2000 caulking gun 3 pcs PUR-O-STOP FS-F 395ml dual cartridge incl. static mixer 20 pcs Hammer-in packer type D12 C; 13.8 x 76.6 mm for bore hole 12 mm; connection quick coupling 1 pc Setting tool for packer with quick coupling type ESH/C 1 pc Protective goggles 1 pc Gloves 1 pc Operation Instructions of PN-2000 1 pc. Technical Data Sheet of PUR-O-STOP FS-F



Legal notice:

The correct and thus successful application of our products is not subject to our control. A guarantee can be issued for the quality of our products within the framework of our sales and supply conditions, however not for successful processing. All data and specifications in this specification sheet are based on the present state of the art and the right to changes and adaptations for the sake of development remains explicitly reserved. The consumption specifications designated by us can be only average empirical values, where deviations are possible on an individual basis and therefore cannot be excluded by us.

TPH Bausysteme GmbH Nordportbogen 8 D-22848 Norderstedt

 Tel.:
 +49 (0)40 / 52 90 66 78-0

 Fax:
 +49 (0)40 / 52 90 66 78-78

 E-Mail
 info@tph-bausysteme.com

 Web
 www.tph-bausysteme.com

